




E-Fujii Farm Lighting Catalogue 2021




Add: CT2B, Nghia Do Urban area, 106 Hoang Quoc Viet, Hanoi City

Hotline: 0983.462.882


Email: haihv.efujii@gmail.com **Website**: www.efujii.com.vn




PARAMETERS



CCT(K)	Power Factor	Warranty
3000 / 4000 / 5000 / 6500	>0.9	5 years
Input Voltage	IP Level	Body
100-240V	IP69K	PC+Alu







Type No.	Length	Power	Efficiency	Lumen	Beam Angle	Dimming	Cover Type	LED
365-0001	1500mm	65W	120lm/W	7800lm	160°	0-10V	Clear	Samsung
365-0003	1500mm	65W	130lm/W	8450lm	130°	0-10V	Frosted	Samsung
365-0005	1500mm	45W	130lm/W	5850lm	130°	0-10V	Frosted	Samsung

MAX AMPERAGE BY VOLTAGE OVERVIEW					
	VOLTAGE(AC)	230V			
European Version	365-0001	0.295A			
European Version	365-0003	0.295A			
European Version	365-0005	0.2A			

MAX CONNECTION QTY.				
	VOLTAGE(AC)	230V		
European Version	365-0001	30pcs		
European Version	365-0003	30pcs		
European Version	365-0005	45pcs		






Weight: 5.29lb/2.4kg
Package dimensions: 1700x40x35mm(20pcs 108.03lb/49kgs)






Suggested cable diameter: 6.5-8.7mm

LIGHT DISTRIBUTION







Designed with a wide beam angle that allows very efficient use by spreading the light evenly across the full width of a poultry house / farm house from a centrally mounted, single row of luminaires. This avoids the hotspots and dark areas typical of batten or pendant lighting and is likely to reduce litter usage.

WHY CHOOSE OUR FARM LITE?

Rated Life

Quality components used within the manufacture of the lighting system, high quality Samsung LEDs provide a service life of in excess of 100,000 hrs when operated at 100% output.

Ammonia Proof

Designed for the poultry industry and common farm house, to accept the harsh environment. High protective level IP69K which means potted, corrosion-proof, clear tube made of PC gives protection against ingression of harming substances and fluids, protected against the degrading effects of Ammonia produced by poultry.

High Installation Efficiency

It can be installed as a single row down the centre or near-centre of the house. This allows for faster installations with fewer materials and lower labour costs than a multi-row system.

Pressure Wash Proof

Withstand washing with high water pressure.

Warranty

5 years warranty.





PRODUCT ACCESSORIES



Stainless clips(1 pair) for surface mounting (365-A-0001)



Stainless clips with silicone pad(1 pair) for mounted on the wirerope (365-A-0004)



M20 PG thread waterproof end cap (365-A-0003)



1.5m adjustable suspending kits (1 pair) for suspending installation (365-A-0002)

